



11625 Spring Cypress Rd.
 Tomball, Texas 77377
 Sales: 713-460-3960
www.NationalChassis.com

DOUBLE DROP FRAME AIR RIDE TANK CHASSIS

GENERAL PARAMETERS

Tare Weight	Approximately 10,700 lbs
GVWR	61,000 LBS
Conspicuity	Meets DOT requirements
Main Beams	Fabricated I-beam
Front, Rear Bolsters	6 in x 8 in structural tubing with buffers, twist locks
Mud Flaps	Plastic anti-sail
Overall Chassis Width, Length	102 in x 42'
Fifth Wheel Height	48 in
Light Attachment, Type	12v truck-lite flange mounted LED

LANDING GEAR

Landing Gear	Two speed AAR approved, square leg. 55,000 lb lift capacity and 160,000 static load capacity
Landing Gear Foot Group	10 in. by 10 in. low profile sandshoe
Lift Device	Lift ready, but not included
Hi-Lo Kit	Hi-Lo ready, but not included
Crank Handle Location	Road side handle

BRAKES

Drum	Outboard mounted
Brake Lining Options	R23
System Type	2S1M

WHEELS

Rims	8 1/4 x 22.5 hub piloted, white
Tires	11R x 22.5

AXLES

Axle Quantity	2 Axles
Axle Locations	49 1/2 in from rear
Kingpin Location	15 in from front of chassis

SUSPENSION

Suspension Type	Air Ride
-----------------	----------

FINISH

Metal Preparation	Clean, dry steel and NACE No. 3 /SSPC-SP-6 "Commercial Blast Cleaning"
Primer	70% Zinc Rich Primer
Topcoat	Urethane
Color	Black